

sensohive



Orbit K

Wireless temperature sensor with type K thermocouple connector

The wireless temperature sensor measures the temperature internally and externally using a type K thermocouple (bought separately).

The sensor can measure temperatures within the range of -200 to 1260 °C¹ using the industry standard type K thermocouple.

The sensor transmits data using the Sigfox-network
sensohive.com/sensors/orbitk

Date: 05-03-2020 // Version: 1.7 // English

Information in this datasheet is based on specifications believed correct at the time of publication. The right is reserved to make changes as design and general improvements are introduced.

Features

- ± 0.3 °C accuracy (internal)
- For external accuracy see the Thermocouple datasheet
- Long battery lifetime²
- Robust design
- Tap functionality for manual update
- Optional: Waterproof tough box

Advantages

- Easy installation and activation
- Versatile use
- Maintenance free
- Low total cost of ownership
- Globally connected³

Configuration Options

The Orbit K is preconfigured with default settings: Data is transmitted to the cloud every 10 minutes (when a type K thermocouple is connected) and includes one measurement per transmission.

Sensohive App

You can easily access all data from your sensors using the Sensohive web application.

Sensohive App features:

- View and export data
- Setup notification alarms
- Setup radio silence alarm
- Locate device (Sigfox Geolocation)

More info: sensohive.com/app

¹ Dependent on the type K thermocouple. Maximum temperature difference between device and probe measurement -200 °C to 1260 °C.

² Requires change of transmission interval (few transmissions/day)

³ Global connection refers to the area covered by Sigfox. Local requirements, legislation, and infrastructures can affect the network availability. Updated outdoor coverage: sigfox.com

Specifications

Sensors	Temperature (Internal) Temperature (external)
Tolerances	± 1.5 °C ⁴
Resolution	0.1 °C
Measurement Range	-200 to 1260 °C (external) ¹
Operating Temperature	-30 to 50 °C
Operating Humidity	0 to 95% RH
Transmission Interval	Every 10 min (adjustable) ⁵
Measurement Interval	Once per transmission
Battery Type	Li-SOCl ₂ , 3.6 V, 5.400 mAh (non-replaceable)
Battery Lifetime	Up to 5 years ⁶
Waterproof	No / Yes with optional tough box
Tap Functionality	Yes
Network	Sigfox
Radio Zones	RC1, RC2, RC4 ⁷
Material Enclosure	ABS plastic (FDA approved)
Dimensions	75 x 26 mm (Ø x H)
Weight	88g
Certifications	CE Sigfox Ready, Class 0 (Best) Radio Equipment Directive (RED) RoHS
Data Access & Analysis	Sensohive App API

⁴ The tolerance of the external temperature sensor depends on the type K thermocouple in use. Standard are around ± 2.2 °C. We offer ready-to-use type K thermocouple wire probes, ± 1.5 °C, Class 1.

⁵ Contact us for more information on adjusting the transmission interval.

⁶ Battery life depends on mode, operating temperature, and frequency of measurements and transmissions. Standard configuration gives a lifetime of up to 8 months with thermocouple inserted 24/7. We guarantee 20.000 measurements or 8 months operation (whichever comes first).

⁷ RC1 is Sigfox Ready certified with Class 0. RC2 and RC4 is pending certification and are available as samples.